**Automatic Needle Threader** 

Needle can be threaded quickly and easily.

**Presser Foot Pressure** 

**Adjustment** 

Presser foot pressure can be adjusted

for better sewing results according to

the type of materials to be sewn.

#### Other Features

Dual LED Lights LED lights brighten the needle area and

sewing area for better material handling.

(F600 only)

Wide variety of built-in Stitch Patterns

Wide variety of stitch patterns including applique, decorative stitches, quilting stitches are built in.

#### Easy Bobbin Thread Winding and Quick Bobbin Preparation

Independent motor winds the bobbin thread. The bobbin preparation is easy. Just follow the guide and it is not necessary to pull up the bobbin thread.



**Random Stitches** 

F600 will create the

width of select quilting

stitch patterns automati-

cally and at random. This

will give your quilting project an enjoyable look without any hassle. (F600 only)

# **HZL-F Series**





-0

	1 000	1 400	1000
Wide table	×	option	option
knee-lifting Lever	×	×	option
Sewing Patterns(font)	225 (4)	157 (3)	106 (3)
LED Lights	2	1	1
Random Stitches	×	-	-
Dimensions	445(W)×290(H)×210(D)mm		
Weight	9.8kg (21.6LBS)		

(Example of HZL-F600)





JUKI CORPORATION 2-11-1,TSURUMAKI, TAMA-SHI, TOKYO, 206-8551, JAPAN http://www.juki.co.jp



rS, iex.html".

JUKI CORPORATION holds the rights to change technical specifications without prior notice.



# Exceed Series

Exceed Dut & Prov



## Thanks to Juki's industrial technology the EXCEED makes it possible to sew quilts beautifully!


#### **Perfect Stitch Quality**



No fabric shrinkage even sewing on extra light Thick handle can be sewn with ease. weight materials.

### Box Feed - Industrial Sewing Machine Technolog

In order to provide beautiful seams and outstanding feed performance, JUKI adopted box feed system. The conventional feed mechanism is oval motion. On the other hand, the box feed moves the feed dog in a box motion. This eliminates material shrinking and shifting. This accurate feeding system provides superior stitch quality for a variety of light to heavy weight fabrics.



**Direct Stitch Pattern Selection** 

1 3 DEF

3 6

# 9

B

Frequently used stitch pat-

terns can be selected

directly through the Direct

3 8

0

Select mode.

₹ 4 6H

PORS

ÄÄ

Free motion sewing with stable thread tensions

#### Wide Sewing Space

HZL-F series has a wider underarm space, with a wider table it is more enjoyable and comfortable to work with large projects. (F600 Standard)





#### Knee-lifting Lever

Presser foot can be raised and loweredbytheknee-liftinglever. Presser foot lift is up to 12 mm when the lever is used. (F600/F400 Standard)

**Presser Foot** 

(F600 Standard)

#### **Accessory Parts for Machine Quilting**



**Walking Foot** (F600/F400 Standard)



**Quilt Presser Foot** (F600/F400 Standard)



**Patchwork Presser Foot** (F600 Standard)



**Edge Sewing Presser Foot** (F600 Standard)

Zigzag stitch for applique

Piecing

Applique

**HZL-F600** 

## For professional sewing results

#### New Function!

#### Foot Controller with thread trimming function

HZL-F series trims both needle and bobbin threads automatically by pressing the heel side of the foot controller. With this feature you can concentrate on your project while automatically cutting the thread





#### **Industrial Quality Buttonholes**

Using a unique sensor method, HZL-F series sews beautiful buttonholes regardless of the type of material and overlapped sections.



.... . **Exceed** Quilt & Pro Special





It is also possible to trim threads with a button located at machine body.

>8

#### Powerful Feeding

HZL-F series has powerful feeding thanks to a special steel feed dog and improved presser foot construction. Heavy material projects, such as hemming denim jeans, can be sewn with ease!



\*16 types of buttonholes are available for your needs



#### **Cutting Width** Adjustment of the buttonhole!!

Now it is possible to adjust the cutting width in 3 steps.

Cutting Width



**Exceed** Quilt & Pro

**Exceed** Home Deco **HZL-F300**