

C-1 C-1A (with Automatic Thread Trimmer)

Direct-drive, 1-needle Lockstitch Machine with Vertical Edge Trimmer



C-1 C-1-TB C-1A

Operation panel and control box are integrated with the machine head



The sewing machine has been integrated with the operation panel and the control box for ease of use. All of the C-1 series adopt the direct drive system. As a result, the sewing machine starts up swiftly and promises increased stop accuracy, responsiveness, thereby demonstrating improved.



C-1, C-1-TB



C-1A

LED light

The LED light is located on the underside of the arm jaw. It reduces operator fatigue and improves work efficiency. It is provided as standard for all models of the C-1 Series.



C-1 C-1-TB C-1A

Easy-to-use vertical edge trimmer

The fabric cutting knife can be easily raised or lowered with the knife lever and bar on the top of the face section of sewing machine, and sewing can be done without using the knife. The knife is capable of cutting any kind of material regardless of its thickness or toughness, including medium-weight material, elastic material and brushing material.



Realizes a dust collection space of 29 mm in width

The C-1 and C-1A have a 29 mm wide dust collection space to support comfortable working.

*The dust collection space of the C-1-TB is 28 mm wide.



Nipper device C-1A

This device pulls the needle thread into the wrong side of the material at the beginning of sewing, thereby ensuring more beautifully-finished seams.



Direct-drive type C-1 C-1-TB C-1A

Since the sewing machine has no V-belt, the operator needs neither to clean up shavings from the V-belt, nor adjust the V-belt tension.

USB port

C-1 C-1-TB C-1A

The C-1A is equipped as standard with a USB port that can be used to charge smartphones, etc.




C-1 USB port



C-1A USB port

SUB-GAUGE SET LIST C-1 C-1A

Specifications of the sub-gauge	Gauge width	Needle plate	Feed dog	Presser foot (asm.)
			• D, F  • H 	• D, F  • H 
D	3.2mm (1/8")	JINPF852013502	JINPF852053301	JINPF8520435
F	4.8mm (3/16")	JINPF852013501		
H	6.4mm (1/4")	JINPF852013503	JINPF030231	JINPF852043501

OPTION DEVICE < for C-1-TB >

Dust suction device (Blower fan motor type): JINPE1414

SPECIFICATIONS

Model name	C-1/C-1-TB	C-1A
Max. sewing speed	4,000 sti/min*	
Max. stitch length	5mm	
Lift of the presser foot	By hand: 5mm / By knee: 13mm	
Needle	DB x 1 (#14) #11~#18	
Lubrication	Automatic	
Lubricating oil	JUKI Machine Oil 7 (equivalent to ISO VG7)	
Power requirement	Single-phase 220V / Single-phase 110V	
Power consumption	392VA	

* sti/min is the abbreviation for "stitches per minute"

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

without automatic thread trimmer

with automatic thread trimmer

Application	Code	Voltage	Code
Medium	M	Single-phase 220V	A
		Single-phase 110V	L

Application	Code	Voltage	Code
Medium	M	Single-phase 220V	A
		Single-phase 110V	L

C-1 [] [] [] [] [] - []

C-1A [] [] [] [] [] - []

Sub-gauge type	Code	Tape binder attachment	Code	Destination	Code
3.2mm (1/8")	D	Provided	TB	General export	A
4.8mm (3/16")	F	Not provided	-	India	F
6.4mm (1/4")	H			Turkey (for RoHS)	H

*Binder can be attached only with sub-gauge type "H".

Sub-gauge type	Code	Auto-lifter	Code	Destination	Code
3.2mm (1/8")	D	Provided	AK	General export	A
4.8mm (3/16")	F	Not provided	-	India	F
6.4mm (1/4")	H			Turkey (for RoHS)	H



JUKI CORPORATION SEWING MACHINERY & SYSTEMS BUSINESS UNIT

2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN PHONE: (81) 42-357-2370 FAX: (81) 42-357-2274 <https://www.juki.co.jp/en>

• Specifications and appearance are subject to change without prior notice for improvement. • Read the instruction manual before putting the machine into service to ensure safety.

• This catalogue prints with environment-friendly soyink on recycle paper. • Paper from responsible sources FSC™ C001712

FEBRUARY, 2024 Printed in Japan(TN)