## Parts Information

Series	Buttonholing Machine	e			
Model	LBH-1790A Series				
Issue No.	A17P-002	Issued by	Sales technical dept.	Data of issue	Mar/23/2017
New Parts	Number	Replaced	Discontinue	C Otł	ner

## **Optional Gauge Added to the LBH-1790AB**

[Models]

•LBH-1790AB

[Description]

Optional gauges have been newly added to the LBH-1790AB (short thread remaining type), onto which materials can be stuck.

By using the presser foot of the LBH-1790A (standard machine), it is possible to prevent the material from displacement on the uneven part.

Since the thickness of the throat plate is the same, there is no effect on the remaining length of the bobbin thread.

	Optional parts			
	Parts subject to	New part names		
P/N	① B1552781000A	40186956	40186955	
	② B1552782000)			
Part name	① Presser foot (Type 1)	Feed plate	Throat plate	
	② Presser foot (Type 2)		Throat plate	
Reference	B1552781000A or B1552782000 40186956 40186955			
Remarks	Needs to be changed to type	Newly added as the option of the	Newly added as the option of the	
	1 or type 2 of the LBH-1790A	LBH-1790AB.	LBH-1790AB. *2	
	(standard machine). *1			

\*1 Presser foot type 1: Sewing length of up to 25mm supported; Presser foot type 2: Sewing length of up to 35mm supported.

\*2 LBH-1790AB (Short thread remaining type) Note that, compared with the standard throat plate of which the supported zigzag width is 5mm at the maximus, the supported zigzag width of the optional throat plate is 4mm at the maximum.



	Old parts (Standard parts)			
P/N	40160113	40160114	40153019	
Part name	Presser foot (AB type 1)	Feed plate	Throat plate	
Reference	Presser foot (AB type 1) Feed plate Throat plate 40160113 40160114 40153019			
Remarks	To be used for LBH-1790AB only	To be used for LBH-1790AB only	To be used for LBH-1790AB only	
	(4mm×25mm)		(Zigzag width of 5mm available)	

## <Changes in the optional parts>

	After change	Before change
Reference	Engraved areas of 0.5mm on the feed plate	Knurling in the feed plate
Knurling of the feed plate	Step machining of 0.5mm	Knurling
Groove width of the feed plate	9.6mm	11.6mm
Throat plate width	8.3mm	10.3





JUKI