

AG-110 CAUTIONS FOR SAFETY

TO ENSURE SAFE USE OF YOUR SEWING MACHINE

For the sewing machine, automatic machine and ancillary devices (hereinafter collectively referred to as "machine"), it is inevitable to conduct sewing work near moving parts of the machine. This means that there is always a possibility of unintentionally coming in contact with the moving parts. operators who actually operate the machine and maintenance personnel who are involved in maintenance and repair of the machine are strongly recommended to carefully read to fully understand the following **SAFETY PRECAUTIONS** before using/maintaining the machine. The content of the **SAFETY PRECAUTIONS** includes items which are not contained in the speciications of your product.

The risk indications are classified into the following three different categories to help understand the meaning of the labels. Be sure tofully understand the following description and strictly observe the instructions.

(I) EXplanation of risk levels



DANGER:

This indication is given where there is an immediate danger of death or serous injury if the person in charge or any third party mishandles the machine or does not avoid the dangerous situation when operating or maintaining the machine.



WARNING:

This indication is given where there is a potentiality for death or serious injury if the person in charge or any third

party mishandles the machine or does not avoid the dangerous situation when operating or maintaining the machine.



CAUTION:

This indication is given where there is a danger of medium to minor injury if the person in charge or any third par- ty mishandles the machine or does not avoid the dangerous situation when operating or maintaining the machine.


(II) EXplanation of pictorial warning indications and warning labels

pictorial warning indication		There is a risk of injury if contacting a moving section.	pictorial warning indication		Be aware that holding the sewing machine during operation can hurt your hands.
	\bigwedge	There is a risk of electrical shock if contacting a high-voltage section.		₽	There is a risk of entanglement in the belt resulting in injury.
	$\underline{\underline{}}$	There is a risk of a burn if contacting a high-temperature section.			There is a risk of injury if you touch the button carrier.
		Be aware that eye deiciency can be caused by looking directly at the laser beam.	Indication label		The correct direction is indicated.
		There is a risk of contact between your head and the sewing machine.			connection of a earth cable is indicated.

Warning label



- There is the possibility that slight to serious injury or death may be caused.
- There is the possibility that injury may be caused by touching moving part.
- ② To perform sewing work with safety guard.
 - To perform sewing work with safety cover.
 - To perform sewing work with safety protection device.
- Be sure to turn the power OFF before carrying out "machine-head threading", "needle changing", "bobbin changing" or "oiling and cleaning".



Electrical-shock danger label

SAFETY PRECAUTIONS

Accident means "to cause i personal injury or death ordamage to property."



 when it is necessary to open the control box containing electrical parts, be sure to turn the power off and wait for ive minutes or more before opening the cover in order to prevent accident leading to electrical shock.



Basic precaution

- Be sure to read the instruction manual and other explanatory documents supplied with accessories of the machine before using the machine. carefully keep the instruction manual and the explanatory documents at hand for quick reference.
- 2. The content of this section includes items which are not contained in the specifications of your product. 3. Be sure to wear safety goggles to protect against accident caused by needle breakage.
- 4. Those who use a heart pacer have to use the machine after consultation with a medical specialist.

safety devices and warning labels

- 1. Be sure to operate the machine after verifying that safety device(s) is correctly installed in place and works normally in order to prevent accident caused by lack of the device(s).
- 2. If any of the safety devices is removed, be sure to replace it and verify that it works normally in order to prevent accident that can result in personal injury or death.
- 3. Be sure to keep the warning labels adhered on the machine clearly visible in order to prevent accident that can result in personal injury or death. If any of the labels has stained or come unstuck, be sure to change it with a new one.

Application and modification

- Never use the machine for any application other than its intended one and in any manner other than that prescribed in the instruction manual in order to prevent accident that can result in personal injury or
 - death. JUKI assumes no responsibility for damages or personal injury or death resulting from the use of the machine for any application other than the intended one.
- 2. Never modify and alter the machine in order to prevent accident that can result in personal injury or death. JUKI assumes no responsibility for damages or personal injury or death resulting from the ma-chine which has been modiled or altered.

Education and training

 In order to prevent accident resulting from unfamiliarity with the machine, the machine has to be used only by the operator who has been trained/educated by the employer with respect to the machine operation and how to operate the machine with safety to acquire adequate knowledge and operation skill.
 To ensure the above, the employer has to establish an education/training plan for the operators and edu-cate/train them beforehand.

Items for which the power to the machine has to be turned off

Turning the power off: Turning the power switch off, then removing the power plug from the outlet.

This applies to the following.

- 1. Be sure to immediately turn the power off if any abnormality or failure is found or in the case of power failure in order to protect against accident that can result in personal injury or death.
- 2. To protect against accident resulting from abrupt start of the machine, be sure to carry out the following operations after turning the power off. For the machine incorporating a clutch motor, in particular, be sure to carry out the following operations after turning the power off and verifying that the machine stops completely.
 - 2-1. For example, threading the parts such as the needle, looper, spreader etc. which have to be threaded, or changing the bobbin.
 - 2-2. For example, changing or adjusting all component parts of the machine.
 - 2-3. For example, when inspecting, repairing or cleaning the machine or leaving the machine.
- 3. Be sure to remove the power plug by holding the plug section instead of the cord section in order to prevent electrical-shock, earth-leakage or ire accident.
- 4. Be sure to turn the power off whenever the machine is left unattended between works.
- 5. Be sure to turn the power off in the case of power failure in order to prevent accident resulting of breakage of electrical components.

PRECAUTIONS TO BE TAKEN IN VARIOUS OPERATION STAGES

Transportation

- 1. Be sure to lift and move the machine in a safe manner taking the machine weight in consideration. Refer to the text of the instruction manual for the mass of the machine.
- 2. Be sure to take sufficient safety measures to prevent falling or dropping before lifting or moving the machine in order to protect against accident that can result in personal injury or death.
- 3. Once the machine has been unpacked, never re-pack it for transportation to protect the machine against breakage resulting from unexpected accident or dropping.

Unpacking

- Be sure to unpack the machine in the prescribed order in order to prevent accident that can result in personal injury or death. In the case the machine is crated, in particular, be sure to carefully check nails. The nails have to be removed.
- 2. Be sure to check the machine for the position of its center of gravity and take it out from the package carefully in order to prevent accident that can result in personal injury or death.

Installation

(I) Table and table stand

- 1. Be sure to use JUKI genuine table and table stand in order to prevent accident that can result in personal injury or death. If it is inevitable to use a table and table stand which are not JUKI genuine ones, select the table and table stand which are able to support the machine weight and reaction force during operation.
- 2. If casters are itted to the table stand, be sure to use the casters with a locking mechanism and lock them to secure the machine during the operation, maintenance, inspection and repair in order to prevent accident that can result in personal injury or death.

(II) Cable and wiring

- 1. Be sure to prevent an extra force from being applied to the cable during the use in order to prevent electrical-shock, earth-leakage or ire accident. In addition, if it is necessary to cable near the operating section such as the V-belt, be sure to provide a space of 30 mm or more between the operating section and the cable.
- 2. Be sure to avoid starburst connection in order to prevent electrical-shock, earth-leakage or ire accident.
- 3. Be sure to securely connect the connectors in order to prevent electrical-shock, earth-leakage or ire accident. In addition, be sure to remove the connector while holding its connector section.

(III) Grounding

- Be sure to have an electrical expert install an appropriate power plug in order to prevent accident caused by earth-leakage or dielectric strength voltage fault. In addition, be sure to connect the power plug to the grounded outlet without exceptions.
- 2. Be sure to ground the earth cable in order to prevent accident caused by earth leakage.

(IV) Motor

1. Be sure to use the specified rated motor (JUKI genuine product) in order to prevent accident caused by burnout.

Before operation

- 1. Be sure to make sure that the connectors and cables are free from damage, dropout and looseness before turning the power on in order to prevent accident resulting in personal injury or death.
- 2. If the table stand with casters is used, be sure to secure the table stand by locking the casters or with adjusters, if provided, in order to protect against accident caused by abrupt start of the machine.

During operation

- 1. Be sure not to put your ingers, hair or clothing close to the moving sections such as the handwheel, hand pulley and motor or place something near those sections while the machine is in operation in order to prevent accident caused by entanglement that can result in personal injury or death.
- 2. Be sure not to place your ingers near the surround area of the needle or inside the thread take-up lever cover when turning the power on or while the machine is in operation in order to prevent accident that can result in personal injury or death.
- 3. The machine runs at a high speed. Never bring your hands near the moving sections such as looper, spreader, needle bar, hook and cloth trimming knife during operation in order to protect your hands against injury. In addition, be sure to turn the power off and check to be sure that the machine completely stops before changing the thread.
- 4. Be careful not to allow your ingers or any other parts of your body to be caught between the machine and table when removing the machine from or replacing it on the table in order to prevent accident that can result in personal injury or death.
- 5. To prevent accidents caused by sudden starting, please make sure to turn off the power when disassembling. After confirming that the sewing machine and motor have completely stopped, proceed with disassembly.
- 6. If a servomotor is used with the machine, the motor does not produce noise while the machine is at rest. Be sure not to forget to turn the power off in order to prevent accident caused by abrupt start of the motor.
- Never use the machine with the cooling opening of the motor power box shielded in order to prevent ire accident by overheat.

Lubrication

- 1. Be sure to use JUKI genuine oil and JUKI genuine grease to the parts to be lubricated.
- 2. If the oil adheres on your eye or body, be sure to immediately wash it off in order to prevent inlamma- tion or irritation.
- 3. If the oil is swallowed unintentionally, be sure to immediately consult a medical doctor in order to pre- vent diarrhea or vomiting.

Maintenance

- In prevention of accident caused by unfamiliarity with the machine, repair and adjustment has to be carried out by a service technician who is thoroughly familiar with the machine within the scope deined in the instruction manual. Be sure to use JUKI genuine parts when replacing any of the machine parts. JUKI assumes no responsibility for any accident caused by improper repair or adjustment or the use of any part other than JUKI genuine one.
- 2. In prevention of accident caused by unfamiliarity with the machine or electrical-shock accident, be sure to ask an electrical technician of your company or JUKI or distributor in your area for repair and mainte- nance (including wiring) of electrical components.
- 3. when carrying out repair or maintenance of the machine which uses air-driven parts such as an air cylinder, be sure to remove the air supply pipe to expel air remaining in the machine beforehand, in order to prevent accident caused by abrupt start of the air-driven parts.
- 4. Be sure to check that screws and nuts are free from looseness after completion of repair, adjustment and part replacement.
- 5. Be sure to periodically clean up the machine during its duration of use. Be sure to turn the power off and verify that the machine and motor stop completely before cleaning the machine in order to prevent accident caused by abrupt start of the machine or motor.
- 6. Be sure to turn the power off and verify that the machine and motor stop completely before carrying out maintenance, inspection or repair of the machine. (For the machine with a clutch motor, the motor will keep running for a while by inertia even after turning the power off. so, be careful.)
- 7. If the machine cannot be normally operated after repair or adjustment, immediately stop operation and contact JUKI or the distributor in your area for repair in order to prevent accident that can result in per- sonal injury or death.
- If the fuse has blown, be sure to turn the power off and eliminate the cause of blowing of the fuse and replace the blown fuse with a new one in order to prevent accident that can result in personal injury or death.
- 9. Be sure to periodically clean up the air vent of the fan and inspect the area around the wiring in order to prevent ire accident of the motor.

operating environment

- 1. Be sure to use the machine under the environment which is not affected by strong noise source (electro- magnetic waves) such as a high-frequency welder in order to prevent accident caused by malfunction of the machine.
- 2. Never operate the machine in any place where the voltage luctuates by more than " rated voltage ±10 %" in order to prevent accident caused by malfunction of the machine.
- 3. Be sure to verify that the air-driven device such as an air cylinder operates at the specified air pressure before using it in order to prevent accident caused by malfunction of the machine.
- 4. To use the machine with safety, be sure to use it under the environment which satisies the following conditions:

Ambient temperature during operation 5°C to 35°C Relative humidity during operation 35 % to 85 %

- 5. Dew condensation can occur if bringing the machine suddenly from a cold environment to a warm one. so, be sure to turn the power on after having waited for a suficient period of time until there is no sign of water droplet in order to prevent accident caused by breakage or malfunction of the electrical components.
- 6. Be sure to stop operation when lightning lashes for the sake of safety and remove the power plug in order to prevent accident caused by breakage or malfunction of the electrical components.
- 7. Depending on the radio wave signal condition, the machine may generate noise in the TV or radio. If this occurs, use the TV or radio with kept well away from the machine.
- 8. In order to ensure the work environment, local laws and regulations in the country where the sewing machine is installed shall be followed.

 In the case the noise control is necessary, an ear protector or other protective gear should be worn ac- cording to the applicable laws and regulations.
- 9. Disposal of products and packages and treatment of used lubricating oil should be carried out properly according to the relevant laws of the country in which the sewing machine is used.

Precautions for safe use of AG-110 sewing machine

A Dangerous	1. To prevent electric shock accidents, please do not touch the motor, host cover, electrical box, or parts inside the operating panel when the power is turned on.
warn	Please do not peek at the light with your eyes. Also, do not use optical instruments to directly observe the light.
pay attention to	 To prevent personal injury, when the sewing machine head is returned to its original position from the state of lifting the sewing machine, Please confirm that there are no tools or components placed under the sewing machine head before returning it to its original position.
	When turning on the power switch and during the operation of the sewing machine, please do not reach your hands under the needle.
	3. After stepping on the pedal, the presser foot moves at high speed. Therefore, when placing the foot on the pedal, please do not place your fingers, face, etc. within the range of the presser foot's movement.
	When folding down the sewing machine head, please make sure to turn off the power switch.
	The operation of the sewing machine is very dangerous. Please do not let your fingers or hair get close to the motor and other driving parts, and do not place objects on the machine.
	6. In the following situations, please immediately turn off the power switch and have maintenance personnel inspect it.
	(1) Frequent occurrences of broken needles and threads.
	(2) Different from normal actions.
	7. When the sewing machine is running, please do not close the air pipe.
	8. Please connect the FG line of the power cable to the ground wire of the main power supply.
	9. Please do not place objects with high heat and humidity near the electrical box.
	During the operation of the sewing machine, please do not let your hands get close to the cutting edge.
	11. Abnormal display of the operating panel may cause machine errors, so please do not turn on or off the power too quickly Close. Please wait for more than 5 seconds after turning off the power before turning it on.
	12. Please make sure to plug and unplug the power plug when the power switch is turned off
	13. As this product belongs to precision machinery, please be careful not to splash water or oil onto the machine during operation, Also, do not let the machine fall and give it an impact.
	14. When operating at a position lower than the machine surface, please be careful not to let your head touch the machine surface, etc.
	15. To prevent personal accidents, please use large machines such as forklifts when lifting or moving machines.
	16. If using this machine in a home environment, there is a possibility of radio interference. At this point, please ask the user to take action Take appropriate measures to solve the problem of radio interference.

Safety devices and warning labels

